

CR3, Charging Rack

Features

Charging Rack (charging only)

- Charges six handsets simultaneously
- Charging status indicated in handset display



Technical Specifications

Physical

Dimensions (l × w × h):	453 × 156 × 98 mm
Weight:	1.6 kg
Material:	Case: PC/ABS
Color:	Light gray

Functional

Supply voltage:	100-240VAC/0.7A 50/60 Hz
Charge current:	0.65 A


Recommended cables

(not supplied by Ascom)	Power cord with IEC C13 connector
-------------------------	-----------------------------------

Environmental

Operating temperature:	+5°C to +40°C
Storage temperature:	-20°C to +65°C
Enclosure protection:	IP30, IEC EN60529
Immunity to electromagnetic fields:	10 V/m EN 301 489-6
Immunity to ESD:	4 kV contact discharge and 8 kV air discharge (EN 301 489-6, EN 61000-4-2)


Compliance to European regulations and standards

EU directives: R&TTE - 1999/5/EC and ErP 2009/125/EC
Product marking: 
Safety: EN60950-1
EMC: EN 55022 (class B), EN 301 489-6

Compliance to US regulations and standards

Product marking: 
Safety: UL 60950-1
EMC: FCC CFR 47 Part 15

Compliance to Canadian regulations and standards

Product marking: 
Safety: CSA 60950-1
EMC: FCC CFR 47 Part 15

Compliance to Australian regulations and standards

Product marking: 
Safety: IEC 60950-1
EMC: EN 55022 (class B), EN 301 489-6

Specifications are subject to change without notice.