

## Data Sheet, CR4 Battery Pack Charger

### Features

- Charges batteries for Advanced DECT handsets<sup>1</sup>
- Charges six batteries simultaneously
- Wall mounted
- LED charging indicator for each display
- Internal power supply
- Easy to wipe clean



---

1."DH4-xxxx" is printed on the handset's label.

### Technical Specifications

#### Physical

Dimensions (l × w × h):	453 × 156 × 98 mm
Weight:	1.4 kg
Material:	Case: PC/ABS
Color:	Light gray

#### Functional

Supply voltage:	100-240VAC/0.7A 50/60 Hz
Charge current:	0.65 A

#### Environmental

Operating temperature:	+5°C to +40°C
Storage temperature:	-20°C to +65°C
Enclosure protection:	IP30, IEC EN 60529
Immunity to electromagnetic fields:	3 V/m EN 61000-4-3
Immunity to ESD:	4 kV contact discharge and 8 kV air discharge (EN61000-4-2)

#### Recommended cables

(not supplied by Ascom) Power cord with IEC C13 connector

**Compliance to European regulations and standards**

EU directives: 2004/108/EC(EMC)

Product marking: 

EN 60950-1

Safety:

EMC: EN 55022 (class B), EN61000-4-3

**Compliance to US regulations and standards**

Product marking:



UL 60950-1

Safety:

EMC: FCC CFR 47 Part 15

**Compliance to Canadian regulations and standards**

Product marking:



CSA 60950-1

Safety:

EMC: FCC CFR 47 Part 15

**Compliance to Australian regulations and standards**

Product marking:



IEC 60950-1

Safety:

EMC: EN 55022 (class B), EN61000-4-3

*Specifications are subject to change without notice.*