



Data sheet



Housing

Size: 210 x 184 x 32 mm
1 HE for 19" systems

Weight: 1050 g

Interfaces

2 x Ethernet: RJ 45 interface 10/100-BASE-TX
(auto negotiation), Power over Ethernet
(802.3af, Class 3)

Slot for Compact Flash Cards Type I

Hardware

Power supply:
Power over Ethernet (802.3af, Class 3)
Power consumption: see wiki-article
„HowTo:Power Consumption“

Digital Signal Processor (DSP) for codec's up
to 60 voice channels

512 MB SDRAM, 32 MB Flash

Operation temperature: 0 °C to +45 °C,
Humidity: 10% to 90%
(not condensed)
Storage temperature: -10 °C to +70 °C

innovaphone PBX

Platform for up to 3200 registrations
Conference server, up to 60 subscribers

Linux Application Platform

for additional software Unified
Communications CTI, ACD and reporting

VoIP protocols

H.323 Version 5
SIP Version 2, conform RFC 3261
SIP over UDP, TCP, TLS, SIPS
RTP, SRTP, RTCP
T.38 (Fax)

Voice Codecs

G.711 A-law / μ -law,
G.729AB,
VAD, CNG,
Dynamic Jitter Buffering
Echo Compensation: G.168

Network

- PPPoE, manual or automatic connection
after boot
- PPTP Tunneling up to 32 tunnels
simultaneously, encoding via MPPE
- NAT, H.323-NAT
- RSTP, IEEE 802.1x
- VLAN-ID (DHCP and LLDP/MED support)
- NTP support

Gateway

- Routing VOIP-VOIP
- Automatic dial tone European and US
Standard
- ENUM for H.323 and SIP protocols
- Plays recorded messages deposited on CF
card or on a web server

Administration

Password protected administration via web-
browser, HTTPS, Kerberos Server

Log and trace files, Display of interface and
connection status, Ping – connection test for
Internet Protocol, Sending SNMP Traps

Save and reload config files, Boot code and
firmware update via HTML upload, Automatic
update via update server

Order number: 01-00010-003