

## Data sheet



### Housing

Size: 210 x 184 x 32 mm  
1 HE for 19" systems

Weight: 1050 g

### Interfaces

2 x Ethernet: RJ 45 interface 10/100-BASE-TX  
(auto negotiation), Power over Ethernet  
(802.3af, Class 3)

Slot for Compact Flash Cards Type I

### Hardware

Power supply:  
Power over Ethernet (802.3af, Class 3)

Digital Signal Processor (DSP) for codec's up  
to 60 voice channels

512 MB SDRAM, 32 MB Flash

Operation temperature: 0 °C to +45 °C,  
Humidity: 10% to 90%  
(not condensed)  
Storage temperature: -10 °C to +70 °C

### innovaphone PBX

Platform for up to 3200 registrations  
Conference server, up to 60 subscribers

### Linux Application Platform

for additional software Unified  
Communications CTI, ACD and reporting

### VoIP protocols

H.323 Version 5  
SIP Version 2, conform RFC 3261  
SIP over UDP, TCP, TLS, SIPS  
RTP, SRTP, RTCP  
T.38 (Fax)

Voice Codecs:  
G.711 A-law /  $\mu$ -law,  
G.729AB,  
VAD, CNG,  
Dynamic Jitter Buffering  
Echo Compensation: G.168

### Network

- PPPoE, manual or automatic connection  
after boot
- PPTP Tunneling up to 32 tunnels  
simultaneously, encoding via MPPE
- NAT, H.323-NAT
- RSTP, IEEE 802.1x
- VLAN-ID
- NTP support

### Gateway

- Routing VOIP-VOIP
- Automatic dial tone European and US  
Standard
- ENUM for H.323 and SIP protocols
- Plays recorded messages deposited on CF  
card or on a web server

### Administration

Password protected administration via web-  
browser, HTTPS, Kerberos Server

Log and trace files, Display of interface and  
connection status, Ping – connection test for  
Internet Protocol, Sending SNMP Traps

Save and reload config files, Boot code and  
firmware update via HTML upload, Automatic  
update via update server

**Order number: 01-00010-003**

**innovaphone® AG**  
Böblinger Straße 76 71065 Sindelfingen  
Tel +49 7031 7 30 09-0 Fax +49 70 31 7 30 09-99  
www.innovaphone.com  
E-mail: info@innovaphone.com