



Data sheet



Housing

Size: 170 x 170 x 38 mm
White plastic
Weight: ca. 400 g

Interfaces

Ethernet: RJ 45 interface 10/100-BASE-TX
(auto negotiation), Power over Ethernet
(max. 5 W)

DECT

GAP / CAP radio interface
Frequencies: 1880-1900 MHz
Up to 8 simultaneously calls
Roaming and handover
On air synchronization
2 x MCX connectors for external antennas
RF output power: 23 dBm - 28 dBm

Hardware

Power over Ethernet or
Local power supply 21 - 56 V DC, max. 5 W

Operation temperature: -10 °C to +55 °C,
Humidity: 15% to 90% (not condensed)
Storage temperature: -25 °C to +55 °C
Storage humidity: 5% to 95% (not condensed)

Administration

Via Web-Browser
Password protected
Administration & software upgrade

VoIP protocols

H.323 version 4
SIP version 2, conform RFC 3261
SIP over UDP, TCP, TLS, SIPS
RTP, SRTP, RTCP
T.38 (Fax)

Voice Codecs

G.711 A-law / μ -law,
G.723.1 (5.3 kbps),
G.729AB,
VAD, CNG,
Dynamic Jitter Buffering
Echo Compensation: G.168

Regulations and standards

EU directives: 1999/5/EC (R&TTE)
Radio: EN 301406
Safety: EN 60950-1
EMC: EN 301 489-6, EN 301 489-1, EN 60945

Additional Features

External LED status indication

Especially designed for innovaphone handsets
IP61 and I63

A selection of character codes provides access
to special features of the innovative PBX such
as group functions such as "pickup", "call on
hold" and "join a dynamic groups".

Order number: 50-01202-001

innovaphone® AG
Böblinger Straße 76, D-71065 Sindelfingen
Tel +49 7031 7 30 09-0 Fax +49 70 31 7 30 09-99
www.innovaphone.com
E-mail: info@innovaphone.com