

	IP61	IP64 (new)
		
Physical	<p>Size: 133 x 53 x 24 mm            Colour: Black            Display: FSTN B/W            28 x 35 mm            112 x 115 pixel            White LED backlight</p>	<p>Size: 137 x 52 x 21.5 mm            Colour: Black            Display: High resolution Colour LCD display            28 x 35 mm            1,8 inch            White LED backlight</p>
Buttons & Keys	<p>3 function keys            On hook, power on / hook off            4 direction navigation            Numeric block            Volume + and -            Ringtone on / off</p>	<p>3 function keys            On hook, power on / hook off            4 direction navigation            Numeric block            Volume + and -            Ringtone on / off</p>
Battery	<p>Type: Li-Ion            Speech time: 16 h            Charge time: &lt;4 h</p>	<p>Type: Li-Ion            Speech time: 16 h            Charge time: &lt;4 h</p>
Interfaces	Headset interface (Standard 2.5 mm)	Headset interface (Standard 3.5 mm)
Radio	<p>Frequency range: 1880-1900 MHz            Modulation: GFSK            Antenna: Integral            Sensitivity: -93 dBm            Dynamic output power: 10 mW (EU)</p>	<p>Frequency range: 1880-1900 MHz            Modulation: GFSK            Antenna: Integral            Sensitivity: -93 dBm            Radiated power: 250 mW (EU)</p>
Environmental	<p>Operating temperature: 0°C to +40°C            Storage temperature: -20°C to +60°C            Enclosure protection: IP40</p>	<p>Operating temperature: 0°C to +40°C            Storage temperature: -20°C to +60°C            Enclosure protection: IP40, IEC EN60529</p>
Order number	50-00061-001	50-00064-004